



Open Roller Cable Guided System

Care and Use Disclaimer

The Open Roller Solar Screen is built to offer years of use while providing the solar blocking and privacy you are looking for!

For the best results please note the following :

1. Your new solar screen will acclimate to your environment. Leave your new screen down for the first 4 hours in direct sunlight to acclimate.
2. Open Roller systems do not have side tracks to tension the fabric. As such, waves in the fabric are to be expected.
3. Strong breezes and winds may cause the fabric to sail slightly. Do not use during high winds.
4. Open roller systems are not intended to protect against rain, bugs or other critters.
5. If your screen gets wet during rains, please allow the fabric to dry before rolling the unit back up to avoid potential mold or mildew growth on surface deposits trapped on your screen.
6. Always watch your screen as it goes up or down, and watch for obstacles that would prevent your screen from functioning fully. Do not leave moving screens unattended.
7. Clean with mild soap and water as needed, rinsing from the inside to the outside first. Heavy stains may be treated with a diluted bleach cleaner (10% or less), 303 Cleaner, or RMR-86 PRO.



-
- I have been shown how to operate the Open Roller Screen
 - I have been told how to care for and maintain the screen, as well as the motorized unit
 - I am aware of the limitations of the Open Roller system
 - I have retained the contact details for my local Installing Dealer representative

Customer Name _____ Dealer Name _____

Address _____ Dealer Phone _____

City / State _____ Installer Name _____

Signature _____ Date _____ Signature _____